

LABELING MACHINE



Top Labeling Machine



Top & Bottom Labeling Machine



Wrap-Around Labeling Machine

SPECIFICATIONS

	Top Labeling Machine	Top & Bottom Labeling Machine	Wrap-Around Labeling Machine
Power	AC 110V/220V 50/60HZ 800W Single Phase		AC 110V/220V 50HZ 900W Single Phase
Air	40 – 80 psi (For optional printer equipment)		
Conveyor Width	180mm (4.72") (Can be set for user's width)		110mm (4.72") (Can be set for user's width)
Dispensing Speed	0 – 36m/minute. Variable Speed Control		
Conveyor Speed	0 – 36m/minute. Variable Speed Control		0 – 25m/minute. Variable Speed Control
Label Length	Min: 10mm (0.39")		Min: 10mm (0.39") Max: 300mm (11.8")
Label Reel Inner	75mm (2.95")		
Label Reel Outer	Max: 375mm (14.76")		
Label Spacer	3mm (0.12") – 5mm (0.20") between labels		
Labeling Speed	36m/(container length + 1cm distance)		25m/(container diameter + 1cm distance) or (label length + 1cm distance)



UTOC (SINGAPORE) PTE LTD

BLOCK2, SKYTECH #08-19, BUKIT BATOK ST 24
SINGAPORE 659480

TEL: (65) 6565 7477, 6569 1691 FAX: (65) 6565 9454
EMAIL: utoc@cyberway.com.sg WEBSITE: www.utoc.sg