

Nozzle Type Vacuuming & Gas Flushing Machine



AZ-450-ES (Stand Table)

This machine can vacuum and pack efficiently your delicate goods, medical, clothes and any other products with protection from oxidation, moisture, external shock and static electricity, etc..

It has developed various type of models which have unique functions and suitable for each of different work conditions. Therefore it is sure that the machine have the best competitive qualities to meet your product line's needs among vacuum machinery.

Specification (AZ-450-ES)

Weight	60 kg
Dimension	520 × 450 × 1020 (W × L × H : mm)
Sealing Length	450 mm (Option : 600, 800 mm)
Sealing Width	5, 10 mm (Option : double heating)
Vacuum Pump	Ejector Pump (Pneumatic) VTX-20
Required Electricity	1 ph, 220V, 50/60Hz (Optional 100~240V)
Required Air Pressure	5~7kgf/cm ²
Vacuum Capacity	7.5 cbm/hr (124ℓ/min)
Max. Instant Consumed Electricity	1.8 ~ 4.0 kw (depend on sealing size)



AZ-450-E (Desk-Top)



AZA-450-ES
(Head Angle Adjustable)



AZH-450-ES
(Plate Height Adjustable)



AZV-600
(Vertical Heavy Duty)

PNV series Model Range

Model No.	Sealing Length (mm)	Sealing Width (mm)	Packing Capacity	Vacuum Pump Type	Required Electricity	Maximum Instant Consumed Electricity	Required Air Pressure
All AZ series	450	5	1~10 ea/min	Ejector (Pneumatic) Oil-Less Oil (Motor)	1ph, 220V, 50/60Hz (100~240V available)	1.8 kw	5~7 kgf/cm ²
		10				2.5 kw	
	600	5				Refer to AZV model	
		10				2.2 kw	
AZV-600	600	5	3.2 kw				
10		2.6 kw					
AZV-800	800	5	3.5 kw				
10		3.0 kw					
AZV-1100	1100	5	4.0 kw				
10							



UTO (SINGAPORE) PTE LTD

BLOCK 2, SKYTECH #08-19, BUKIT BATOK ST 24
SINGAPORE 659480

TEL: (65) 6565 7477, 6569 1691 FAX: (65) 6565 9454

EMAIL: utoc@cyberway.com.sg WEBSITE: www.utoc.sg